

12 Cup Automatic Coffee Brewer with 2 Warmers



Model OL

Shown with decanters
(decanters sold separately)

Dimensions: 23.5" H x 12" W x 18.5" D

Features

12 Cup Automatic Coffee Brewer

- Brews 4.0 to 7.5 gallons (15.1 to 28.4 liters) of perfect coffee per hour.
- All stainless steel construction.
- Can also be operated as a pourover unit.
- Designed to function well in low or uneven water pressure situations.
- SplashGard® funnel deflects hot liquids away from the hand.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12⁷/₁₆" H x 2¹/₂" W x 3" D

31.6 cm H x 6.35 cm W x 7.62 cm D



Paper Filter Pack

Product No. : 20115.6000

Packed per case: 1,000

Dimensions: 4¹/₄" Base x 2³/₄" Sidewall

10.8 cm Base x 6.98 cm Sidewall



WX1-warmer

Product No. : 06450.6000

One position warmer



WX2-warmer

Product No. : 06310.6000

Two position warmer



Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

20.95 cm H x 5.87 cm Dia.



Easy Pour® black decanter

Product No. : 06100.0201

Quantity: 1 (also packaged in quantities of 3 & 24)



Easy Pour® orange decanter (for decaf)

Product No. : 06101.0201

Quantity: 1 (also packaged in quantities of 3 & 24)



Model

Agency Listing

OL20



OL35



Dimensions & Specifications



Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity per hour	Cubic ft ³ /m ³	Weight lbs/kg	Cord Attached
OL 20	20820.6000	120	18.8	1800	2250	5.1 gal/19.3 liter	6.5 / .18	35 / 15.9	No
OL 35	20820.6002	120/240	15.6	3500	3750	7.5 gal/28.4 liter	6.5 / .18	35 / 15.9	No

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Electrical: OL 20 requires 2-wires plus ground service rated 120V, single phase, 60Hz.

OL 35 requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60Hz.

Plumbing: 10-90 psi (138-621 kPa). Supplied with 1/4" male flare fitting.

